

sewoo

3-Inch POS Printer

# SLK-TS100



- High Performance Easy Maintenance
- Easy maintenance with Jam release lever
- Easy maintenance for paper jam
- High speed printing at 8.6ips (220mm/sec)
- Ergonomic Design Entry-level Printer
- Simple and easy replacement of components including head, motor, cutter, PCB, etc
- Ideal for top exit printing with wall mount



Barcode



Durable



Paper  
Width



Easy  
Loading



Fast  
Speed



Compact  
Design



Easy  
Maintenance

## APPLICATION



## SPECIFICATIONS



### PRINTER CHARACTERISTICS

#### Print Method

Direct thermal

#### Print Speed

220mm/sec

#### Print width

2.83"(72mm,  
adjustable by commands)

#### Resolution

203 dpi

#### Power

Power type : External SMPS

AC : 110~220Vac 50/60Hz

DC : 24Vdc / 2.5A

#### Sensor

Paper end, Cover open

#### Reliability

TPH life : 100km

MCBF : 80,000H

Cutter life : 1.5 Million cuts

#### Drawer port

1circuit (24V,1A Max)



### PHYSICAL CHARACTERISTICS

#### Dimension (W x D x H)

5.59" x 7.28" x 5.35"  
(142 x 185 x 136mm)

#### Weight

2.25b(1.02Kg)



### INTERFACES

1. USB(B type)+  
Serial(RS-232C\_9pin)
2. USB(B type)+Serial  
(RS- 232C\_9pin)+  
Ethernet Built-in



### CERTIFICATIONS

CE, FCC, KC



### OPERATING CHARACTERISTICS

#### Operating Temperature

32 ~ 113°F(0 ~ 45°C)

#### Operating Humidity

10 ~ 80RH%

#### Storage Temperature

14 ~ 140°F(-10 ~ 60°C)

#### Storage Humidity

10 ~ 90RH%



### MEDIA CHARACTERISTICS

#### Media Type

Thermal receipt paper

#### Media Width

79.5±0.5mm

#### Media Core Diameter

0.68 ~ 0.7"(17.5 ~ 18mm)

#### Media Roll Diameter

3.1"(ø 80mm)

#### Thickness

0.06~0.08mm



### SOFTWARE

#### Emulations

ESC/POS Command compatible

#### Drivers

Windows Driver

(9X, 2000, 2003, XP, 7, 8, 10)

#### SDK

Win, iOS, Android



### BARCODES

#### 1D

EAN-8, EAN-13, Code 39,

Code 93, Code 128, ITF,

UPC-A, UPC-E, Codabar

#### 2D

PDF 417, QR code



### FONTS / GRAPHICS

#### Character Type

Font A(12x24), Font B(9x17),

Chinese(Traditional/Simplified, 24x24),

Korean(24x24), Japanese(24x24)

#### Characters per line (CPL)

Font A(12x24) : 48cpl or 42cpl,

Font B(9x17) : 64cpl,

Chinese/Korean/Japanese: 24cpl

#### Character set

95 Alphanumeric,

16 International,

128 x 18 Graphic



### ACCESSORIES

#### Standard

Melody box

# sewoo

Republic of Korea [Head Office / R&D Center]

28-6, Gajangsaneopdong-ro, Osan-si, Gyeonggi-do, 18103, Republic of Korea

T. +82-31-8077-5000 F. +82-31-624-5310 E. sales@miniprnter.com

www.miniprnter.com

نماینده رسمی فروش و خدمات پس از فروش در ایران | شرکت زیراسیا ۴۴۲۳ ۷۵۵۶ (۰۲۱)

