

Print On-The-Go: Maximize productivity with the Ultra-Compact, Ultra-Light

LK-P25

2-Inch Mobile Receipt Printer



KEY FEATURES

CHARGING



5-PIN
MICRO USB



1.8M

DROP
RATING



LEATHER
CASE
+
SHOULDER
STRAP

Ultra portable Ultra flexible

- 5-Pin micro -USB : Compatible with smart phone, tablet and other peripherals.
- Easy pairing process using NFC Tag.
- Long battery life : 3.7V / 2,600mAh. Rechargeable Li-ion battery.
- Print entire shift : Print over 160 meters via Bluetooth with fully charged battery.

Seamless communication

- Simultaneously connect to multiple peripherals via Bluetooth 4.2 classic and Low Energy (BLE).
- Compatible with Android,iOS and Windows operating systems.

Ultra-compact design

- Ultra Compact and Lightweight : 0.19kg including battery
79x44.4x103.2 mm / 3.1x1.7x4 inch
- Drop rating :
5ft/1.5m (unit only) to concrete
6ft/1.8m with case to concrete
- Sturdy belt clip for comfortable fit.

LK-P25 2-Inch Mobile Receipt Printer

SPECIFICATIONS

PRINTER CHARACTERISTICS

Print Method

Direct thermal

Print Speed

Up to 2.3ips (60mm/sec)

Print width

Up to 1.8" (48mm)

Resolution

203 dpi (8dots/mm)

Memory

256KB SRAM, Flash

Battery Voltage / Capacity

3.7V / 2600mAh.

Rechargeable Li-ion battery

Battery Charge time

Adaptor : Max. 3.4Hrs

USB : Max. 5.7Hrs

Standby Time

79Hrs

Sensor

Paper end, Cover open,

Black mark

Reliability

TPH life : 50km

INTERFACE

Standard

USB,

Bluetooth 4.2 classic

and Low Energy (BLE)

ACCESSORIES

Standard

Charger(USB Cable), Battery pack,

Thermal roll paper,

Belt clip & Battery cover

Option

Leather case

MEDIA CHARACTERISTICS

Media Type

Thermal paper

Media Width

2.2" (58mm)

Media Core Diameter

0.4" (12.5mm)

Media Roll Diameter

1.5" (40mm)

Thickness

0.06mm

OPERATING CHARACTERISTICS

Operating Temperature

14 ~ 122°F(-10 ~ 50°C)

Operating Humidity

10 ~ 80%

Storage Temperature

-4 ~ 140°F(-20 ~ 60°C)

Storage Humidity

10 ~ 90%

Drop Rating

5ft/1.5m (unit only) to concrete

6ft/1.8m with case to concrete

AGENCY APPROVALS

KCC, CE, FCC, UL/cUL, Mfi

PHISICAL CHARACTERISTICS

Dimension (W x D x H)

3.1"×1.74"×4.06" (79×44.4×103.2mm)

Weight (Kg)

0.4lb(0.9kg, With battery)

SOFTWARE

Emulation

ESC/POS

Driver

Windows Driver(10, 2012, 8, 7, 2008, VISTA,

2003, XP, 32bit & 64bit), Window CE &

Mobile Driver & SDK (CE 4.2~, Mobile 5.0~),

Linux Driver, Mac Driver,

OPOS Driver, JavaPOS Driver

SDK

iOS, Android(2.1~), Windows,

Linux, Blackberry, Symbian

BARCODE

1D

UPC-A, UPC-E, EAN-8, Code39, Code93, ITF,

Codabar, EAN-13, Code128

2D

QR, PDF417, Maxicode, Datamatrix

FONT / GRAPHICS

Character size

Font A(12x24), Font B(9x17),

Chinese(Traditional/Simplified, 24x24),

Korean(24x24), Japanese(24x24)

Characters per line (CPL)

Font A(12x24): 32cpl,

Font B(9x17): 42cpl,

Chinese / Korean / Japanese: 16cpl

Character set

95 Alphanumeric,

14 International,

128 x 18 Graphic



J.stephen

Republic of Korea [Head Office]

28-6, Gajangsaneopdong-ro,
Osan-si, Gyeonggi-do, 18103,
Republic of Korea

T. +82-31-8077-5000

F. +82-31-624-5310

E. sales@miniprnter.com

México

Paseo de la Reforma No. 265 Piso 2.
Oficina SBC. Col. Cuauhtémoc,
C.P. 06500 Ciudad de Mexico

T. +52-1-55-3232-9543

E. sales@miniprnter.com

North America

20280 S. Vermont Ave. STE 200,
Torrance, CA 90502, USA

T. +1-310-561-8030

E. sales@miniprnter.com

www.miniprnter.com