




WP260

Thermal Receipt Printer

- IAP update online
- Support queuing function
- Support QR code, PDF417
- With the function of avoiding missing orders
- Supports IP modification across network segments
- With print-head over temperature protection function





Wp260

Thermal Receipt Printer



Printing WP260	
Printing method	Direct thermal
Printer width	80mm
Column capacity	576 dots/line
Printing speed	260mm/s
Interface	USB+Serial+Lan / Bluetooth/WiFi Optional
Printing paper	79.5±0.5mm x ø80mm
Line spacing	3.75mm(Adjustable by commands)
Print command	ESC/POS
Column number	80mm paper: Font A - 42 columns or 48 columns/ Font B - 56 columns or 64 columns/ Chinese, traditional Chinese - 21 columns or 24 columns
Character size	ANK, Font A: 12×24 dots Font B: 9×17 dots Simplified/Traditional Chinese: 24x24 dots
Cutter	
Auto cutter	Partial
Barcode Character	
Extension character sheet	PC347(Standard Europe)/Katakana/PC850(Multilingual)/PC860(Portuguese)/ PC863(Canadian-French)/PC865(Nordic)/West Europe/Greek/Hebrew/East Europe/ Iran/WPC1252/PC866(Cyrillic#2)/PC852(Latin2)/PC858/IranII/Latvian/Arabic/PT151(1251)
1D code	UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODE39/ITF/CODABAR/CODE93/CODE128
2D code	QR Code / PDF417
Buffer	
Input buffer	128 Kbytes
NV Flash	256Kbytes
Power	
Power adaptor	AC: 100-240V, 50~60Hz
Power source	Output: DC 24V/2.5A
Cash drawer output	DC 24V/1A
Physical characteristics	
Weight	1 KG
Dimensions	190.16(D)*140(W)*134.64(H)mm
Environmental Requirements	
Work environment	Temperature (0~45℃) humidity(10~80%)(non-condensing)
Storage environment	Temperature(-10~60℃) humidity(10~90%)
Reliability	
Cutter life	1.5 million cuts
Printer head life	150KM
Driver	Win 9X / Win 2000 /Win 2003 /Win XP /Win 7 /Win 8 /Win 10/Linux



Guangzhou Winprt Technology Co., Ltd.
Address: Room 616, NO.80 JinGang Road,
Nansha District, Guangzhou, Guangdong, China.
<http://www.winprt.com>
Email:sales2@winprt.com

